



Bower Products Limited.
Unit 31, Abbey Industrial Estate, Woodside End,
Wembley Middx., HA0 1ZD. UK.

Tel: 44 (0)20 8903 0983 Fax: 44 (0)20 8903 1592
Email: enquiry@bower.co.uk
Web: www.bower.co.uk

Fly-shield

The *Insect-a-clear* **FLY-SHIELD** range comprises of three models, the **FLY-SHIELD 1, 2** and **4**. It is the ideal alternative to conventional high voltage machines. Models 1 and 2 are suitable for front of house flying insect control where discreet management is required. The Model 4 is suitable for larger areas where suspending the machine gives a massive 360 sq metre approx. coverage. The flying insects are attracted to the special ultra violet light that is irresistible to flying insects. Once attracted into the **FLY-SHIELD** they will come to rest on a special adhesive coated glue board and become permanently captured. Once the board is full it can quickly and easily be replaced. Once removed, monitoring by a pest controller or hygiene manager is easily undertaken.

The following features are incorporated on the *Insect-a-clear* **FLY-SHIELD**

The **FLY-SHIELD 1 & 2** can be wall mounted or suspended

The **FLY-SHIELD 4** can only be suspended

All stainless steel construction.

Easy servicing, just remove lift off the shield for easy glue board replacement.

Board life up to 3 months depending on environmental conditions and infestation.

Shatter resistant tube option available.

Plastic fly killers can degrade and become brittle due to the effect of the ultra violet light. This model, being all steel, is unaffected by this.

Conforms BS EN 60598-1 1993 and the European EMC directive.

Full 2 year guarantee (except tubes).

Order Codes

FG1CBS	FLY-SHIELD 1 with standard tubes .
FG2CBS	FLY-SHIELD 2 with standard tubes.
FG4SBS	FLY-SHIELD 4 with standard tubes.
FG1CSS	FLY-SHIELD 1 with shatter resistant tubes.
FG2CSS	FLY-SHIELD 2 with shatter resistant tubes.
FG4SSS	FLY-SHIELD 4 with shatter resistant tubes.
MG1TRA	Pack of 6 replacement boards for the FLY-SHIELD 1
MG2TRA	Pack of 6 replacement boards for the FLY-SHIELD 2 Note: The FLY-SHIELD 4 uses 2 of the FLY-SHIELD 2 boards.

Specification

	FLY-SHIELD 1	FLY-SHIELD 2	FLY-SHIELD 4
Protected area	Up to 90 sq. metres	Up to 180 sq. metres	Up to 360 sq. metres
Voltage	230v a.c	230v a.c	230v a.c
Total wattage	40	70	120
Blacklight tubes	1 off 18 watt LYNX	2 off 18 watt LYNX	4 off 18 watt LYNX
Height	250 mm	250 mm	470 mm
Width	345 mm	585 mm	650
Depth	115 mm	140 mm	140 mm
Weight	4 kilo	6 kilo	10 kilo
Finish	Stainless steel	Stainless steel	Stainless steel
Guarantee	2 years (except tube)	2 years (except tube)	2 years (except tube)

Packing details

Height			
Width			
Depth			
Weight			